

## **Coadd™ D-6037**

Dispersing Agent

### **DESCRIPTION**

**Coadd™ D-6037** is a hydrophobically modified polyacrylic polymer. It has good dispersing effect, with excellent water resistance. Due to the hydrophobically modification, the product has excellent early-stage water resistance and early-stage scrub resistance, also the rain imprint resistance has been improved. It also has excellent formulation compatibility, and color development performance.

### **PHYSICAL PROPEERTIES**

Appearance	Light yellow liquid
Density (g/ml)	1.04
Active content (%)	29
Viscosity (25°C, mPas)	<500

Note: These properties are only typical, and do not represent product specifications

### **APPLICATION CHARACTERISTIC AND ADVANTAGES**

**Coadd™ D-6037** is recommended for dispersing of inorganic pigment/fillers in water-borne architecture, wood and industrial coatings, with high requirement in early-stage water resistance. It can be used solely, or combined with other acrylic type dispersant to achieve more comprehensive performance.

Suggested dosage (base on the pigment volume): 3-10%

Above dosage are only for orientation, optimum level of dosage should be determined via laboratory tests.

### **SAFETY NOTICE**

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

### **DISCLAIMER**

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

**\*\*Please refer to SDS for more information**