

Coadd™ D-6228

Wetting and Dispersing Agent

DESCRIPTION

Coadd™ D-6228 is a pigments wetting and dispersing agent with high pigment affinity groups. It is suitable for water-borne coating and color pastes with steric hindered effect. It can also be used in resin containing grinding systems. The product has good wetting, color development with pigments, and good compatibility with different emulsions. Can effectively prevent floating.

PHYSICAL PROPEERTIES

Appearance	Light yellow liquid
Density (g/ml)	1.13
Active content (%)	90
Viscosity (3# ,60rpm, 25℃)	500-3000

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ D-6228 is recommended for the dispersing of organic pigments and carbon black. It can also be used in resin free grinding systems. It can provide good compatibility and stability, avoid floating. The product also recommended in inorganic pigments color pastes with Dispersant D-6151, help for pigments wetting, viscosity reducing and stability improving.

Suggested dosage (base on the pigment):

Organic pigments: 10 – 50%; Carbon black: 10 – 50%.

Optimum level of dosage should be determined via a series of laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly know and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**