

Coadd™ DF-0211

Defoaming Agent

DESCRIPTION

Coadd™ DF-0211 is a mixture of modified polysiloxane with hydrophobic solids, VOC-free. It is suitable for waterborne high gloss system, overprint varnishes and dispersion adhesives, with strong foaming destroying properties and good compatibility with acrylate emulsion binders.

PHYSICAL PROPERTIES

Form	Off-white Liquid
Density (g/ml)	1.05
Active content (%)	100
Viscosity(Brookfield #2,60rpm,25℃)	<1000

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ D-0211 is recommended for high gloss and satin-gloss systems, and suitable for airless applications. Effective in pigment color concentrations. Recommended to be added in grinding stage to avoid defects.

Suggested dosage base on the total of solid pigments and fillers formulation: 0.1 – 0.8%.

Optimal levels are determined through laboratory tests.

Separation may occur with long storage time, mix well before use.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**