

Coadd™ DF-6038

Defoaming agent

DESCRIPTION

Coadd™ DF-6038 is mixture of silicone and paraffin based mineral oils with hydrophobic components. The product is APEO-free & VOC-free, suitable for water-borne emulsion coating & paint systems, with PVC between 30 – 70.

PHYSICAL PROPERTIES

Form	Cloudy yellowish liquid
Density (g/ml)	0.9
Active content (%)	100
Flash point (°C)	>100

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-6038 is recommended for water-borne emulsion system in coatings, with universal use in emulsions that are APEO-free. The product has incorporated with silicone, which enhanced its defoaming performance. Especially recommended in high gloss and paints emulsion system, also can be used in emulsion binders. Separation may occur, should mix well before use.

Suggested dosage base on the total of solid pigments and fillers formulation: 0.1 – 0.5%.

Dosage may be up to 0.8%. Optimal levels are determined through laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**