

Coadd™ DF-6048

Defoaming Agent

DESCRIPTION

Coadd™ DF-6048 is waterborne dispersion defoamer containing mineral oil, silicone and hydrophobic components. Suitable for aqueous emulsion paints, adhesives and building and construction coatings. Especially effective for emulsion paints with mid to high PVC content.

PHYSICAL PROPERTIES

Appearance	Light yellowish liquid
Density (g/ml)	0.96
Active content (%)	51%
Viscosity (mPa.s, 25°C)	<5000

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-6048 is VOC free. Recommended for polyacrylate emulsion paints: architecture, building and construction, and is also suitable for polyacrylate emulsion parathion process. The product is recommended to be added separately in grinding and let-down stage, sufficient shear force needed to avoid defects formation.

The product is temperature sensitive, transportation and storage should be kept between 0 - 40°C.

Suggested dosage (base on the total formulation): 0.1 – 0.5%. Optimum dosage should be determined via a series of laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly know and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**