

Coadd™ DF-6094

Defoaming Agent

DESCRIPTION

Coadd™ DF-6094 is a modified siloxane type polymer defoamer with hydrophobic solids. The product is VOC-free, suitable to be used in water-borne coating systems. It is a compatible defoamer, with good effect in long-term foam destroying. Suitable for different purpose especially effective in eliminating micro-foams in printing ink and coating applications.

PHYSICAL PROPERTIES

Form	Light yellowish cloudy liquid
Density (g/ml)	1.03
Active content (%)	100
Flash point (°C)	>100

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-6094 is recommended for water-borne coatings with both pigmented and non-pigment systems, also has good effect in printing inks and overprint varnishes. The product can be added at any time during the production process, and can prevent foam forming during manufacture and application. The product may experience separation under long-term storage. Mix well before use.

Suggested dosage base on the total formulation: 0.1 – 0.5%

Optimal levels are determined through laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**