

Coadd™ DF-6226

Defoaming Agent

DESCRIPTION

Coadd™ DF-6226 is a silicone-free polymer based defoaming agent. The product has high defoaming efficiency, good foam inhibition and bubble burst performance. It also provides good compatibility and leveling. The product can be diluted in water, suitable for industrial coating and pigment concentrates.

PHYSICAL PROPERTIES

Form	Colorless to light yellow liquid
Density (g/ml)	1.02
Active content (%)	100
Viscosity (25°C, mPa.s)	<1000

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-6226 has excellent foam inhibition and bubble burst performance at low viscosity. Suitable for water-borne pigments, inks and industrial coatings.

Sedimentation may occur after long time storage, mix well before use.

Suggested dosage base on the total of solid pigments and fillers formulation: 0.2 – 5.0%

Optimal levels are determined through laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**