

Coadd™ DF-6601

Defoaming Agent

DESCRIPTION

Coadd™ DF-6601 is a emulsion defoaming agent containing polysiloxane,. The product is VOC free, suitable for water-borne coating and adhesives. Compared with mineral oil defoamers, this product shows better water dispersing property and better foam suppressing. Very suitable for water-borne emulsion systems with PVC range between 30-70.

PHYSICAL PROPEERTIES

Appearance	Light yellow emulsion
Density (g/ml)	1.02
Active content (%)	20
Viscosity (mPa.s, 25°C)	<5000

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-6601 is recommended for water-borne coating and adhesive systems, such as emulsion paints, gloss, semi-gloss paints and plasters. Similar application and performance compared with mineral oil defoamers. The product is recommended to add in both grinding and let-down stage.

The product is temperature sensitive, transportation and storage need to be kept between 0-40°C.

Suggested dosage (base on the total formulation): 0.1 – 0.5%. Optimum dosage should be determined via a series of laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and

safe. For your reference, the above information is only for commonly know and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**