

Coadd™ DF-8001

Defoaming Agent

DESCRIPTION

Coadd™ DF-8001 is an organo-modified siloxane defoaming agent, suitable for applications using lubricates and cooling fluid with defoaming requirement, particularly suitable for water-borne systems. The product has 100% active content, with excellent defoaming efficiency and foam inhibition properties.

PHYSICAL PROPERTIES

Form	off-white liquid
Density (g/ml)	1.01
Active content (%)	100
Viscosity(25°C/mPa.s)	<8000

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-8001 is recommended for metal-work fluids, textile auxiliaries, surfactant concentrates and other industrial applications. The product can be incorporated into the formulation, or post addition. It gives excellent defoaming and foam inhibition performance, with no adverse effect on the finishing process.

Suggested dosage base on the total formulation: 0.1 – 1.0%, or 0.001 - 0.1% when post addition as tank side defoamer. Optimal levels should be determined via laboratory tests.

Separation may occur with long storage time, please mix well before use.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**