

Coadd™ DF-8600

Defoaming Agent

DESCRIPTION

Coadd™ DF-8600 is a foam destroying polysiloxanes containing hydrophobic solids. It is suitable for solvent-borne and water-borne systems and high solid systems. The product contains silicone and is VOC free. It is especially recommended for 100% UV and matt system. It has rapid foam destroying in thick aqueous architecture emulsion coatings and solvent free epoxy flooring coatings.

PHYSICAL PROPERTIES

Form	Off-white liquid
Density (g/ml)	1.0
Active content (%)	100
Viscosity(Brookfield #2,60rpm,25℃)	<5000

Note: These properties are only typical, and do not represent product specifications

APPLICATION CHARACTERISTIC AND ADVANTAGES

Coadd™ DF-8600 has strong defoaming performance, suitable for wide applications like aqueous emulsion paints, wood & furniture solvent-borne and solvent free coatings, solvent free epoxy flooring coatings, roof coatings. The product has strong defoaming performance for both macro & micro foams in epoxy, polyurethane and polyaspartic acid esters. Recommend add in grind stage with high shear force for the product to be distributed evenly.

Please check compatibility before use, may cause formation of pinholes.

Suggested dosage base on the total of solid pigments and fillers formulation: 0.05 – 0.5%.

Optimal levels are determined through laboratory tests.

SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and

safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

****Please refer to SDS for more information**